

BESKRIVELSE

Total tykkelse	EN 428	mm	6.00
Tykkelse slitesjikt	EN 429	mm	0.70
Vekt	EN 430	g/m ²	9895
Flisstørrelse	EN 427	mm	
Staverstørrelse	EN 427	mm	176 x 1000
Antall fliser/pakke	-	-	
Antall staver/pakke	-	-	8





KLASSIFISERING

Norm	-	-	EN 649
Europaklasse	EN 685	-	34 - 43
Brannklassifisering	EN 13 501-1	klasse	
Elektrostatisk oppladning	EN 1815	kV	< 2
Friksjon, våt	DIN 51 130	klasse	R9

TESTVERDIER

Slitestyrke	EN 660.2	mm ³	≤ 2
Slitasjegruppe	EN 649	gruppe	T
Dimensjonsstabilitet	EN 434	%	≤ 0.15
Inntrykksfasthet	EN 433	mm	0.10
Trinnlydsdemping	EN ISO 717-2	dB	6
Varmemotstand	EN 12524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Kjemikaliebestandighet	EN 423	klasse	Good
Overflatebehandling	-	-	PUR

CE MARKING

	EN 14041	-	  
		-	